



苏州思普瑞电子科技有限公司

SUZHOU SIPURUI ELECTRONICS TECHNOLOGY CO.,LTD.

地址：苏州市高新区狮山路金狮大厦25D室013

**ADD: ROOM 013, 25D, JINSHI BUILDING, SHISHAN ROAD,
SUZHOU HIGH-TECH ZONE**

WhatsApp: +86 153 8026 6877

Email: sprxue@gmail.com

**PROFESSIONAL SWITCH POWER
SUPPLY MANUFACTURER**

LRS-35W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
199X98X38MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ
240~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH
WEIGHT/PACKING
0.2KG/92PCS/20KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-35-5	5V, 0~7A	±2%	80mVp-p	78%
LRS-35-12	12V, 0~3A	±1%	120mVp-p	82%
LRS-35-15	15V, 0~2.4A	±1%	120mVp-p	86%
LRS-35-24	24V, 0~1.5A	±1%	150mVp-p	88%
LRS-35-36	36V, 0~1A	±1%	200mVp-p	88%
LRS-35-48	48V, 0~0.8A	±1%	200mVp-p	88%

LRS-50W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
99X82X30MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ
240~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH
WEIGHT/PACKING
0.2KG/92PCS/20KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-50-5	5V, 0~10A	±1%	80mVp-p	82%
LRS-50-12	12V, 0~4.2A	±1%	120mVp-p	84%
LRS-50-15	15V, 0~3.4A	±1%	120mVp-p	86%
LRS-50-24	24V, 0~2.2A	±1%	150mVp-p	86%
LRS-50-36	36V, 0~1.45A	±1%	200mVp-p	88%
LRS-50-48	48V, 0~1.1A	±1%	200mVp-p	88%

LRS-75W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
99X97X30MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ
240~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH
WEIGHT/PACKING
0.25KG/66PCS/18KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-75-12	12V, 0~6A	±1%	120mVp-p	84%
LRS-75-15	15V, 0~5A	±1%	120mVp-p	86%
LRS-75-24	24V, 0~3.2A	±1%	150mVp-p	86%
LRS-75-36	36V, 0~2.1A	±1%	200mVp-p	88%
LRS-75-48	48V, 0~1.6A	±1%	200mVp-p	88%

LRS-100W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
129X98X38MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ
240~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH
WEIGHT/PACKING
0.3KG/54PCS/17KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-100-12	12V, 0~8.5A	±1%	120mVp-p	82%
LRS-100-15	15V, 0~7A	±1%	120mVp-p	84%
LRS-100-24	24V, 0~4.5A	±1%	150mVp-p	86%
LRS-100-36	36V, 0~2.8A	±1%	200mVp-p	88%
LRS-100-48	48V, 0~2.3A	±1%	200mVp-p	88%

LRS-150W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100-120VAC/200-240VAC (SWITCH)
50/60HZ 255~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC

WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH

WEIGHT/PACKING
0.45KG/36PCS/18KG

DIMENSION
159X97X30MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-150-12	12V, 0~12.5A	±1%	150mVp-p	84%
LRS-150-15	15V, 0~10A	±1%	150mVp-p	84%
LRS-150-24	24V, 0~6.5A	±1%	200mVp-p	86%
LRS-150-36	36V, 0~4.3A	±1%	200mVp-p	86%
LRS-150-48	48V, 0~3.3A	±1%	200mVp-p	86%

LRS-200W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100-120VAC/200-240VAC (SWITCH)
50/60HZ 255~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

OVER TEMPERATURE PROTECTION
≥85°C±10°C CUT OFF OUTPUT AUTOMATIC RECOVERY

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC

WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH

WEIGHT/PACKING
0.7KG/30PCS/22KG

DIMENSION
215X115X30MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-200-12	12V, 0~17A	±1%	150mVp-p	82%
LRS-200-15	15V, 0~14A	±1%	150mVp-p	82%
LRS-200-24	24V, 0~8.8A	±1%	150mVp-p	86%
LRS-200-36	36V, 0~5.9A	±1%	200mVp-p	86%
LRS-200-48	48V, 0~4.4A	±1%	200mVp-p	88%

LRS-350W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100-120VAC/200-240VAC (SWITCH)
50/60HZ 255~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC

WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH

WEIGHT/PACKING
0.7KG/30PCS/22KG

DIMENSION
215X115X30MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-75-12	12V, 0~6A	±1%	120mVp-p	84%
LRS-75-15	15V, 0~5A	±1%	120mVp-p	86%
LRS-75-24	24V, 0~3.2A	±1%	150mVp-p	86%
LRS-75-36	36V, 0~2.1A	±1%	200mVp-p	88%
LRS-75-48	48V, 0~1.6A	±1%	200mVp-p	88%

LRS-400W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100-240VAC 50/60HZ
240~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.6KVAC

WORKING TEMP HUMIDITY
-10°C~+60°C,20%~90%RH

WEIGHT/PACKING
0.7KG/20PCS/16KG

DIMENSION
215X115X30MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
LRS-350-12	12V, 0~29A	±1%	150mVp-p	80%
LRS-350-15	15V, 0~23.2A	±1%	150mVp-p	82%
LRS-350-24	24V, 0~14.6A	±1%	150mVp-p	84%
LRS-350-36	36V, 0~9.7A	±1%	200mVp-p	86%
LRS-350-48	48V, 0~7.3A	±1%	200mVp-p	88%

DR-15W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
159X97X30MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
INRUSH CURRENT
COLD STARTING CURRENT 25A/115 V 45A/230V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,10%~80%RH
WEIGHT/PACKING
0.1KG/172PCS/19KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
DR-15-5	5V, 0~3A	±2%	80mVp-p	77%
DR-15-12	12V, 0~1.25A	±1%	120mVp-p	84%
DR-15-15	15V, 0~1A	±1%	120mVp-p	83.50%
DR-15-24	24V, 0~0.63A	±1%	150mVp-p	85%

DR-60W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
78X93X56MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
INRUSH CURRENT
COLD STARTING CURRENT 18A/115 V 36A/230V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,10%~80%RH
WEIGHT/PACKING
0.27KG/50PCS/15KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
DR-60-5	5V, 0~6.5A	±2%	100mVp-p	80%
DR-60-12	12V, 0~5A	±1%	120mVp-p	82%
DR-60-15	15V, 0~4A	±1%	120mVp-p	83%
DR-60-24	24V, 0~2.5A	±1%	150mVp-p	84%

DR-30W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
78X93X56MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
INRUSH CURRENT
COLD STARTING CURRENT 15A/115 V 30A/230V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,10%~80%RH
WEIGHT/PACKING
0.25KG/50PCS/14KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
DR-30-5	5V, 0~3A	±2%	100mVp-p	74%
DR-30-12	12V, 0~2A	±1%	120mVp-p	81%
DR-60-15	15V, 0~2A	±1%	120mVp-p	82%
DR-30-15	24V, 0~1.5A	±1%	150mVp-p	83%

DR-75W

SINGLE OUTPUT SWITCHING POWER SUPPLY



DIMENSION
55.5X125X100MM (L*W*H)

INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
OVERVOLTAGE PROTECTION
15V~16.5V|29~34V|58~65V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,10%~80%RH
WEIGHT/PACKING
0.5KG/30PCS/18KG

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
DR-75-12	12V, 0~6.3A	±2%	100mVp-p	76%
DR-75-24	24V, 0~3.2A	±1%	150mVp-p	80%
DR-75-48	48V, 0~1.6A	±1%	240mVp-p	81%

DR-120W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
OVERVOLTAGE PROTECTION
15V~16.5V|29-33V|58-62.5V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,10%~80%RH
WEIGHT/PACKING
0.65KG/20PCS/15KG

DIMENSION
65.5X125.2X100MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
DR-120-12	12V, 0~10A	±2%	80mVp-p	80%
DR-120-24	24V, 0~5A	±1%	80mVp-p	84%
DR-120-48	48V, 0~2.5A	±1%	100mVp-p	85%

EDR-75W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
INRUSH CURRENT
COLD STARTING CURRENT 20A/115V 35A/230V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC
WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH
WEIGHT/PACKING
0.45KG/36PCS/18KG

DIMENSION
32X125.2X102MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
EDR-75-12	12V, 0~6.3A	±1%	80mVp-p	85%
EDR-75-24	24V, 0~3.2A	±1%	120mVp-p	86%
EDR-75-48	48V, 0~1.6A	±1%	150mVp-p	88%

DR-240W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
OVERVOLTAGE PROTECTION
15V~16.5V|29-34V|58-65V
OVER TEMPERATURE PROTECTION
≥85°C±10°C CUT OFF OUTPUT AUTOMATIC RECOVERY
INRUSH CURRENT
COLD STARTING CURRENT 40A/230V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC
WORKING TEMP HUMIDITY
-10°C~+60°C,10%~80%RH
WEIGHT/PACKING
1.0KG/12PCS/15KG

DIMENSION
125.5X125.2X100MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
DR-240-24	24V, 0~5A	±1%	100mVp-p	84%
DR-240-48	48V, 0~2.5A	±1%	120mVp-p	85%

EDR-120W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC
OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY
OVERVOLTAGE PROTECTION
20A/115V 35A/230V
WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC
WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH
WEIGHT/PACKING
0.55KG/30PCS/18KG

DIMENSION
40X125.2X113.5MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
EDR-120-12	12V, 0~10A	±1%	100mVp-p	85%
EDR-120-24	24V, 0~5A	±1%	120mVp-p	87%
EDR-120-48	48V, 0~2.5A	±1%	150mVp-p	88.00%

EDR-150W

SINGLE OUTPUT SWITCHING POWER SUPPLY



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 40A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.55KG/30PCS/18KG

DIMENSION
40X125.2X113.5MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
EDR-150-12	12V, 0~12.5A	±1%	150mVp-p	80%
EDR-150-24	24V, 0~6.5A/220VAC	±1%	150mVp-p	87%
	24V, 0~5.2A/110VAC	±1%	150mVp-p	87%
EDR-150-48	48V, 0~3.2A	±1%	150mVp-p	87%

NDR-120W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 20A/115V 35A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.55KG/30PCS/18KG

DIMENSION
40X125.2X113.5MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
NDR-120-12	12V, 0~10A	±1%	100mVp-p	85%
NDR-120-24	24V, 0~5A	±1%	150mVp-p	86%
NDR-120-48	48V, 0~2.5A	±1%	150mVp-p	88%

NDR-75W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 40A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.45KG/36PCS/18KG

DIMENSION
32X125.2X102MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
NDR-75-12	12V, 0~6.3A	±1%	80mVp-p	85%
NDR-75-24	24V, 0~3.2A	±1%	120mVp-p	86%
NDR-75-48	48V, 0~1.6A	±1%	150mVp-p	88%

NDR-240W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 20A/115V 35A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
1.0KG/12PCS/14KG

DIMENSION
63X125.2X113.5MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
NDR-240-24	24V, 0~10A	±1%	150mVp-p	88%
NDR-240-48	24V, 0~5A	±1%	150mVp-p	90%

MDR-20W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 20A/115V 40A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.16KG/72PCS/14KG

DIMENSION
22.5X90X100MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
MDR-20-5	5V, 0~3A	±2%	80mVp-p	76%
MDR-20-12	12V, 0~1.67A	±1%	120mVp-p	80%
MDR-20-15	15V, 0~1.34A	±1%	120mVp-p	80%
MDR-20-24	24V, 0~1A	±1%	150mVp-p	82%

MDR-40W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 30A/115V 60A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.28KG/50PCS/16KG

DIMENSION
40X90X100MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
MDR-40-5	5V, 0~6A	±2%	80mVp-p	78%
MDR-40-12	12V, 0~3.3A	±1%	120mVp-p	85%
MDR-40-24	24V, 0~1.7A	±1%	150mVp-p	86%
MDR-40-48	48V, 0~0.83A	±1%	200mVp-p	88%

DUE TO SPACE LIMITATIONS, PLEASE CONSULT FOR MORE PRODUCTS+86 153 8026 6877

THE PRODUCTS INFORMATION IS JUST FOR REFERENCE

MDR-60W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 30A/115V 60A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.3KG/50PCS/17KG

DIMENSION
40X90X100MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
MDR-60-5	5V, 0~10A	±2%	80mVp-p	77%
MDR-60-12	12V, 0~5A	±1%	120mVp-p	85%
MDR-60-24	24V, 0~2.5A	±1%	150mVp-p	86%
MDR-60-48	48V, 0~1.25A	±1%	200mVp-p	87%

MDR-100W

SINGLE OUTPUT INDUSTRIAL DIN RAIL



INPUT VOLTAGE RANGE
100~240VAC 50/60HZ 140~340VDC

OVERLOAD PROTECTION
115~150% HICCUP MODE CUT OFF OUTPUT AUTOMATIC RECOVERY

INRUSH CURRENT
COLD STARTING CURRENT 30A/115V 60A/230V

WITHSTAND VOLTAGE
I/P-O/P: 1.5KVAC
I/P-FG: 1.5KVAC
O/P-FG: 0.5KVAC

WORKING TEMP HUMIDITY
-15°C~+65°C,10%~80%RH

WEIGHT/PACKING
0.38KG/30PCS/13KG

DIMENSION
55X90X100MM (L*W*H)

MODEL	OUTPUT	DIFFERENCE	RIPPLE COEFFICIENT	EFFICIENCY
MDR-100-12	12V, 0~7.5A	±1%	120mVp-p	80%
MDR-100-24	24V, 0~4A	±1%	150mVp-p	84%
MDR-100-48	48V, 0~2A	±1%	200mVp-p	86%

DUE TO SPACE LIMITATIONS, PLEASE CONSULT FOR MORE PRODUCTS+86 153 8026 6877

THE PRODUCTS INFORMATION IS JUST FOR REFERENCE